



Rotary hoe

Avant rotary hoe is the basic attachment for soil cultivating, seed bed finishing and rotovating. Adjustable cultivating depth up to 150 mm.

Can be equipped with a field roller which compacts the ground after cultivating.

- **An inexpensive and robust rotary hoe**



Working width	1000 mm	1300 mm
Working depth	50 - 150 mm	
Weight	160 kg	180 kg
Product no	A2808	A21163

Optional extras:

- Field roller for 1000 mm rotary hoe A2972
- Field roller for 1300 mm rotary hoe A21164

Model	220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	eS	e6	
1000																										
1300																										



Very compatible



Compatible



Incompatible



Stone burier

A professional hydraulic stone burier for preparation of lawn beds. The stone burier mills the soil, buries eventual stones and other objects up to 150 mm depth in a single pass, making a milled and tamped topsoil. Working depth is steplessly adjustable with the rear field roller. With the optional seeding unit you are able to make a ready lawn surface on one pass.

Stone buriers are most commonly used when the topsoil needs to be milled thoroughly. The soil is milled more thoroughly and deeper than with a rotary harrow.

- **Professional, efficient stone burier**
- **Top grade finish with just one pass**
- **Can be equipped with seeding unit → ready lawn surface in a single pass**



Optional extras:

- Seeding unit for 1130 mm model (A21011)
- Seeding unit for 1300 mm model (A21238)
- Seeding unit for 1500 mm model (A410304)

Model	1130	1300	1500
Working width	1130 mm	1300 mm	1500 mm
Roller width	1320 mm	1500 mm	1700 mm
Working depth	0 - 150 mm		0-160 mm
Weight	218 kg	250 kg	290 kg
Weight with seeding unit	250 kg	290 kg	330 kg
Product no	A21010	A21237	A410303

Model	220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6	
1130																										
1300																										
1500																										

Very compatible
 Compatible
 Incompatible



Rotary harrow

Avant rotary harrow is an excellent leveler for lawn beds, yards, gardens etc. – for places where the ground needs to be perfectly levelled. It harrows only the topsoil and gives a very nice finish for sowing. Required output is lower than that of the stone burier which allows also a higher working speed. Working depth is adjusted with the rear field roller which levels the seeding bed during operation. With the optional seeding unit you are able to make a ready lawn surface on one pass.

Rotary harrows are most commonly used for lighter topsoil levelling. The soil is normally not milled as deep or as thoroughly as with a stone burier.

- Professional, efficient rotary harrow for topsoil levelling
- Top grade finish with just one pass
- Can be equipped with seeding unit → ready lawn surface in a single pass
- Requires less power than stone burier



Optional extras:

- Seeding unit for 1350 mm model (A21085)
- Seeding unit for 1500 mm model (A21193)
- Seeding unit for 1700 mm model (A415800)

Model	1200	1350	1500	1700
Working width	1050 mm	1220 mm	1400 mm	1550 mm
Roller width	1200 mm	1350 mm	1500 mm	1700 mm
Working depth	0-160 mm			
Weight	180 kg	220 kg	250 kg	280 kg
Weight with seeding unit	-	260 kg	290 kg	320 kg
Product no	A21067	A21077	A21185	A21431

Model	220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6
1200	Green	Green	Green	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
1350	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
1500	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red
1700	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red	Red



Very compatible



Compatible



Incompatible



Leveller

A simple and inexpensive but incredibly useful and efficient attachment for levelling and planing of larger areas. With Avant leveller you can easily and quickly level sand, mulch etc. The leveller is most commonly used in:

- Preliminary lawn bed levelling
- Yard sand levelling
- Driveway levelling

The leveller can also be used for lifting job site materials like sod rolls, tools etc.

- **Economical attachment for levelling gravel and other soil materials**
- **Eliminates almost all manual shoveling at job sites**



Width	Weight	Product no
1200 mm	85 kg	A3241 I
1500 mm	95 kg	A33537

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6	



Very compatible



Compatible



Incompatible



Roller compactor

The roller compactor with mesh roller is a practical attachment for compacting soil when preparing for lawn seeding and right after lawn seeding. You are able to compact soil with the full 1500 mm width of the roller and push down with the whole weight of the loader's front axle.

The other roller compactor model is equipped with a plain, hollow roller which can be filled with water (max. 167 l). It is useful for preparing and compacting a newly installed sod and similar surfaces where a plain roller is a must and mesh rollers cannot be used. Both compactors can also be fitted with max. 4 pcs of Avant 29 kg back weights. The compactors can also be towed, if needed, with the A37481 drawbar mounted on the compactor.

- Easy and economical compacting of lawns before and after seeding with the mesh roller
- Plain roller is useful for compacting a newly installed sod and similar surfaces; can be filled with water
- Both models can also be towed with the A37481 drawbar
- 4 pcs Avant 29 kg back weights can be mounted to add weight

New



Model	Mesh roller	Plain roller
Working width	1500 mm	1500 mm
Total width	1605 mm	1605 mm
Roller diameter	400 mm	406 mm
Length	610 mm	610 mm
Weight, without extra weights and water	100 kg	196 kg
Water volume	-	167 l
Product no	A37064	A37488

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6	

Very compatible
 Compatible
 Incompatible



Front rake

Front rake is an uncomplicated and economical attachment for levelling of sand and gravel driveways, anywhere you want to have a nice looking finish. The spring loaded tines rake and level the ground efficiently. The rake can also be used for loosening and levelling of uneven soils.

There are two models available: one with normal tines and other with HD tines. The rake with stronger HD tines will also collect branches etc. heavier material when levelling the ground.

- **Uncomplicated and economical leveller for sand gravel driveways**
- **Works on soils as well**
- **Two models available: with normal tines or with stronger HD tines**
- **Can be mounted on all Avante models**



New

Model	Standard	HD
Width	2000 mm	2000 mm
Tine height	245 mm	420 mm
Total height	560 mm	695 mm
Weight	35 kg	56 kg
Product no	A36968	A37357

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6	





Ripper

The ripper is an inexpensive and practically irreplaceable tool in ground works. With the ripper it is easy and effortless to remove roots as well as rocks even from hard packed ground. The replaceable hard metal teeth guarantee a long lifespan for the attachment.

The ripper is operated by pressing the three blades into the ground next to the object you wish to remove. When the teeth have sunk into the ground, tilt the ripper inwards and then lift the boom upwards which will bring the object on top of the ground.

- **An inexpensive tool for removing of rocks, tree stumps, roots etc. from the ground**
- **Eliminates a huge amount of manual work**



Width	500 mm
Working depth	appr. 300 mm
Weight	50 kg
Product no	A44412

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6	



Very compatible



Compatible



Incompatible



Screening bucket

The new Avant screening bucket is a fast and efficient compact system for screening and blending soils, aggregates and compost. The durable and flexible star-shaped plastic Poly Star rollers screen without shredding the vegetation or crushing the aggregates into the finished screened product.

The unique design fitted with sealed bearings, self tensioning carbon belt driveline and flexible Poly Stars enables for a large screening area to create a low maintenance, fast and efficient screening system.

- **Separates stone/soil/vegetation**
- **Screens without crushing or shredding**
- **Suitable for different types of soil**



Width	1410 mm
Bucket volume	258 l
Screening area	1200 x 430 mm
Weight	390 kg
Product no	A36503

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6



New

Landscaping



Stump grinder

Avant stump grinder is an efficient and easy to operate tree stump remover. The cutting disc is mounted crosswise in relation to the loader, which means it throws the wood waste to the right side – the waste doesn't fly on the operator or the loader. In addition, the stump grinder is equipped with a protective rubber cover which prevents the wood from flying around.

Grinding happens by moving the grinder forward and backward which means easy control with the drive pedals of the loader – or with the tilt movement of the quick attach plate, and the sideways mounting of the cutting disc guarantees excellent visibility to the working area. Cutting teeth have three cutting edges: once a tooth becomes blunt, its fastening bolt is easy to open and turn the tooth so that a sharp cutting edge comes into use.

- Equipped with \varnothing 540 mm cutting disc with 20 pcs replaceable teeth
- Teeth have three cutting edges – once a tooth becomes blunt it can be turned to get a new sharp cutting edge
- Excellent visibility to the work area, easy to operate
- Rubber damper on the quick attach bracket minimizes vibrations to the loader and makes working smoother



Cutting disc diameter	540 mm
Number of teeth	20 pcs
Width	840 mm
Height	920 mm
Length	630 mm
Weight	168 kg
Product no	A37265

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6



Very compatible



Compatible



Incompatible



Stump buster

A new safer and faster way of removing tree stumps!

The stump buster is an efficient, easy and safe way for removing tree stumps. The three blade drill head has slow speed and high torque, which means it can be used within confined spaces and pedestrian areas safely.

The stump buster drills either a 250 mm or a 350 mm diameter hole into the tree stump, shaving off the wood as it turns.

The drive unit is equipped with a hydraulic motor and planetary gearbox which guarantee high torque and efficient cutting. The drill shaft is 500 mm long and the bolt-on blades are replaceable. Blades are made from extra hard material, they can be sharpened and have a longer life cycle also in harder conditions.



- **New, safe way for removing of tree stumps**
- **Uncomplicated design, easy to operate**
- **Bolt-on, replaceable blades**

Model	XHD92
Max. torque	5873 Nm
Drive shaft length	500 mm
Weight	300 kg
Drive unit product no.	A33571

Drills:

Drill Ø 250 mm, A36763

Drill Ø 350 mm, A36764

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6	





Stone grab

The mechanical stone grab is easy to mount on the Avant jib boom. Thanks to the powerful gripping force it can handle concrete components, kerb stones, natural stones, tombstones etc.

The stone grab is equipped with:

- Lifting eye for attaching to Avant jib boom hook
- Automatic load release
- Changeable rubber covered steel grabs
- Spring loaded bolt for quick and easy opening width adjustment

The stone grab is best mounted on an Avant with telescopic boom. With the Avant jib boom (A32395) and telescopic boom extended the max. outreach is 2100 mm, measured from the front wheel. When using the telescoping Avant jib boom A21342 maximum outreach is as high as 3050 mm.

ATTENTION! Avant jib boom (A32395 or A21342) is required for lifting of the stone grab.



- **Scissor type lifting device for:**

- Kerb stones
- Concrete components
- Tombstones
- Natural stones

- **Scissor mechanism is completely mechanical, doesn't require hydraulics**

Gripping width	50 - 480 mm
Jaw height	170 mm
Jaw length	420 mm
Lifting capacity	900 kg
Weight	55 kg
Product no	A21179

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6



Very compatible



Compatible



Incompatible



Stone installation clamp

With the hydraulic installation clamp you can lay paving stones quickly and efficiently. The installation clamp takes a whole layer of paving stones directly from a pallet, which can then be lifted on to the area to be paved.

The hydraulic installation clamp is equipped with:

- adjustable side grippers for the exact shaping of the installation pattern.
- hydraulic rotation
- ADV pushing off device. The ADV presses the blocks into the laying course automatically once the clamp is opened – this way the cocking of the blocks can be avoided and a lot of time is saved, because one doesn't have to reposition the blocks by hand.

- **For professional and fast stone laying**
- **Minimizes hand labour and intensive manual lifting**



Gripping width	575 - 1245 mm
Total width	990 - 1480 mm
Lifting capacity	400 kg
Weight	230 kg
Product no	A37539

Requires attachment control switch pack on the loader

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6





Grabbing tool

Grabbing tool is mainly intended for lifting and handling of round objects. It is especially suited for lifting of barrels and plant and tree pots. Grabbing force can be adjusted, which means all kinds of objects can be handled without damaging them.

Grabbing tool is equipped with two smaller, rubber padded grabs which allow handling of smaller and more fragile objects as well. When the grab is opened completely it can take larger objects like barrels, bigger plant pots etc.

- **Easiest way to lift and transport plants, trees, barrels etc. without damaging them**
- **Excellent tool for nurseries and landscapers**
- **With the optional tilt adapter it is also possible to rotate the objects max. 90 degrees**



Option:

Conical grabbers – for objects with conical shape like plant pots A421030

Barrel grabbers – for completely round objects like barrels A421031

Tilt adapter 90 degrees A36505

(requires second auxiliary hydraulics outlet in the front)

Min. grab diameter	250 mm
Max. grab diameter	1200 mm
Max. load	650 kg
Weight	95 kg
Product no	A34290

220	225	225LPG	313S	320S	320S+	420	423	520	523	525LPG	528	530	R20	R28	R35	630	635	640	745	750	755i	760i	e5	e6	



Very compatible



Compatible



Incompatible



AVANT[®]

AVANT Tecno OY
Ylotie 1
33470 YLOJARVI
FINLAND

Tel. +358 3 347 8800
sales@avanttecno.com



AVANT has a policy of continuing improvement,
and retains the right to change specifications without notice.
© 2018 AVANT Tecno Oy. All rights reserved.

www.avanttecno.com